KENWORTH

MHC Kenworth - Chattanooga T652
7831 LEE HIGHWAY

CHATTANOOGA, Tennessee United States 37421
Phone: (423) 698-4461
Fax:
Email:

MILLER INDUSTRIES TOWING EQUIP
8503 Hilltop Dr

Ooltewah, Tennessee United States 37363
Phone: (423) 238-4171
Fax:
Contact Email:
Prepared for: VINCE TIANO

Vehicle Summary

Unit

Model:	T400 Series Conventional.
Type:	FULL TRUCK
Description:	****2019 T440 CA190 LCG20

Application

Intended Serv.:	Local pickup & delivery. Vehicles which haul
Commodity:	Heavy machinery

Body

Type:	Van
Length (ft):	28.0
Height (ft):	13.5
Max Laden Weight (lbs):	4000

Trailer

No. of Trailer Axles:	0
Type:	
Length (ft):	0.0
Height (ft):	0.0
Kingpin Inset (in):	0
Corner Radius (in):	0

Restrictions

Length (ft):	120
Width (in):	102
Height (ft):	13.5

Chassis

Fr Axle Load (lbs):	20000
Rr Axle Load (lbs)	40000
G.C.W. (lbs):	66000
Road Conditions:	
Class A (Highway)	89
Class B (Hwy/Mtn)	11
Class C (Off-Hwy)	00
Class D (Off-Road)	00
Maximum Grade:	6
Wheelbase (in):	264
Overhang (in):	80
Fr Axle to BOC (in):	73
Cab to Axle (in):	191
Cab to EOF (in):	271
Overall Comb. Length (in):	394

Special Req.

U.S. Domestic Registry, 50-State

Approved by: _____ **Date:** _____

Note: All sales are F.O.B. designated plant of manufacture.

PACCAR FINANCIAL

Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com.

PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/27/2017 11:30:52 AM	***Complete***	Model Number:	T400 Series Conventional.
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q72765328
Prepared by:	ID: jervin		Version Number:	40.30

KENWORTH

MHC Kenworth - Chattanooga T652	**MILLER INDUSTRIES TOWING EQUIP**
7831 LEE HIGHWAY	**8503 Hilltop Dr**
CHATTANOOGA, Tennessee United States 37421	**Ooltewah, Tennessee United States 37363**
Phone: (423) 698-4461	**Phone: (423) 238-4171**
Fax:	**Fax:**
Email:	**Contact Email:**
	Prepared for: VINCE TIANO

	Description	Weight
Model		
	T400 Series Conventional.	11,511
	T440 6x4 Class 8	0
	CARB Idle Emissions Reduction Feature for PX-7 and PX-9	0
	T440 6x4 Class 8	0
	Heavy machinery	0
	Local pickup & delivery. Vehicles which haul freight, typically operating within a 100-mile radius, on public streets & highways, & other paved surfaces, including limited Class C roads. Includes package & freight delivery, as well as fuel oil or petroleum distribution, etc. Road usage: minimum 3% Class B, do not code for Class D.	0
	Van	0
	U.S. Domestic Registry, 50-State	0
Engine & Equipment		
	PACCAR PX-9 380 2017 380@1900 1250@1400	0

Includes turbo exhaust brake, no code is used. Diagnostic Plug for data link, Oil Cooler, Aluminum Flywheel Housing.

N09200 N205 120..Standard Maximum Speed Limit [LSL]
N09220 N207 0....Expiration Distance
N09240 P09 120...Hard Maximum Speed Limit
N09260 P14 78...Maximum Accelerator Pedal Vehicle Speed
N09280 P16 0....Accelerator Lower Droop
N09300 P19 78...Maximum Cruise Speed
N09320 C143 0....Cruise Control Lower Droop
N09360 N203 252..Reserve Speed Function Reset Distance
N09380 N202 0....Maximum Cycle Distance
N09400 N206 10...Maximum Active Distance
N09420 N201 0....Reserve Speed Limit Offset
N09440 P11 YES..Engine Protection Shutdown
N09460 P06 NO...Gear Down Protection
N09480 P26 1150.Max PTO Speed
N09500 P02 NO...Cruise Control Auto Resume
N09520 P04 NO...Auto Engine Brake in Cruise
N09540 N209 0....Expiration Distance
N09560 P520 YES..Enable Idle Shutdown Park Brake Set
N09580 P32 5....Timer Setting
N09600 P233 YES..Enable Impending Shutdown Warning

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/27/2017 11:30:52 AM	***Complete***	Model Number:	T400 Series Conventional.
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q72765328
Prepared by:	ID: jervin		Version Number:	40.30

	Description	Weight
	N09620 P234 60...Timer For Impending Shutdown Warning N09640 P516 35...Engine Load Threshold N09680 P33 NO...Idle Shutdown Manual Overrule N09720 P230 YES..Enable Hot Ambient Automatic Overrule N09740 P46 40...Low Ambient Temperature Threshold N09760 P56 60...Intermediate Ambient Temperature Threshold N09780 P47 80...High Ambient Temperature Threshold	
	Prospector Version 40.3 Replaces 40.2	0
	Effective VSL Setting NA	0
	Engine Idle Shutdown Timer Disabled	0
	Enable EIST Ambient Temp Overrule	0
	Enable EIST in PTO Mode Use only with MX and Cummins engines	0
	Eff EIST NA Expiration Miles Use only with MX and Cummins engines	0
	Air compressor: Cummins 18.7 CFM For Cummins And PACCAR PX engines.	0
	Engine mount Powercore air cleaner. w/constant torque SS clamps, pop-up air restriction indicator. Pop-up indicator is standard.	0
	Fan Hub: Horton 2-Speed for ISL9, ISL-G, PX-8 or PX-9	0
	Cooling module: 1300 square inches. Includes aluminum radiator core, aluminum charge air cooler, translucent surge tank and washer bottle, silicone hoses, and extended life coolant. Drain valve is not available w/Allison transmissions.	0
	Bug screen: Front of grille on C500 ,T800, T880, and W900. Behind grille on T660, T680, and T300 (Medium Duty).	2
	Exhaust: 2017 EPA RH Under DPF/SCR w/ RH side of vertical cab tailpipe w/ daycabs, extended daycabs, or modular sleepers.	0
	Tailpipe: 7 in. single 36 in. 45 degree curved.	4
	Fuel Filter:Fleetguard FS1003 Fuel/Water Separator for PX-9	0
	Run Aid:None *For Fuel Filter	0
	Start Aid:None *For Fuel Filter	0
	Kenworth Fuel Cooler Required for Cummins engines with a single fuel tank. Required for PACCAR MX-13 engine with a single fuel tank and stationary use: High RPM, low vehicle speed, sustained for longer than 1 hour. Optional for all other applications.	6

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/27/2017 11:30:52 AM	***Complete***	Model Number:	T400 Series Conventional.
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q72765328
Prepared by:	ID: jervin		Version Number:	40.30

	Description	Weight
	Immersion block heater 120V 1000W w/plug under door on C500, T660, T800 & W900.	0
	Retarder Jacobs for PX-8/9 ISL w/ 3-way switch.. Replaces the standard turbo brake for PX-8 engines.	57
	Alternator: Bosch 200 amp, brush type	0
	Batteries: 3 PACCAR GP31 threaded post (700-730) 2100-2190 CCA dual purpose.	57
	Starter: PACCAR 12 volt electrical system. W/ centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0
	Multi-function engine connector for body builder interface for Cummins.	0
	Body Builder Control Harness coiled EOF for customer installed remote throttle and remote PTO controls. Harness includes Remote PTO control and Remote Throttle controls. T680/T880 models do not require 12-way engine connector sales codes. All other models require (1900082 or 1900084).	2
	Jump start terminals under hood.	12
Transmission & Clutch		
	Fuller Advantage Automated FAO-14810C-EA3 10SPD No Cooler w/ HSA *Use w/ 2250385 Only.	367
	Clutch:UltraShift Plus Or Fuller Advantage Series Automated transmissions.	0
	Driveline: 3 Dana SPL250XL W/ 2 centerbearings Requires 3500057 interaxle driveline. Low maintenance offering from Spicer. On-highway 350K mi first service interval, 100K mi subsequent service interval on U-joint, splines lubed for life, quick disconnect end caps.	0
	Chassis will be fitted w/ LH transmission PTO. (Prevents ECU F/Interfering w/ PTO Only).	0
	Chassis will be fitted w/RH transmission PTO. (Prevents ECU F/Interfering W/PTO Only)	0
	Rear transmission support springs for transmission PTO applications are required to ensure that engine flywheel housings are not overloaded when transmission PTO's are installed.	0
Front Axle & Equipment		
	Dana Spicer D2000 Front Axle rated 20K standard track.	120
	Front Brakes: 14,601-22K Bendix air disc brakes.	10
	Splined rotor for front air disc brakes for use with iron hubs.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/27/2017 11:30:52 AM	***Complete***	Model Number:	T400 Series Conventional.
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q72765328
Prepared by:	ID: jervin		Version Number:	40.30

	Description	Weight
	Front Hubs Iron hub pilot 20,000 lbs. 10 Bolt 16.5x6in. or 7in. or air disc brakes. 10 Bolt, 11-1/4 in. bolt circle. Consider Wheelguards (5850002) with aluminum wheels.	80
	ConMet PreSet Plus Hub package; front axle.	0
	Hubcap: front vented.	0
	Slack Adjusters included w/ front axle or brake. Also use w/ disc brakes.	0
	Front Springs: Taperleaf 20K w/ shock absorbers w/ maintenance-free elastomer spring pin bushings. Standard with rubber pins except for C500 which has threaded pins. W900S only. Not available on W900L. W900B use 2866021.	241
	Dual power steering gears: 20K Sheppard M100P.	70
	Power Steering Cooler:Radiator Mounted Air-to-Oil	11
	Threaded Bushings for taperleaf spring 16K, 18/20K, 22K, 40K replacing rubber.	0
Rear Axle & Equipment		
	Dual Dana Spicer DSP41 rear axle rated at 40K. (DSP40 w/ heavy-wall housing) w/ 11mm housing and 1.88in. shaft diameter. Tandem rear axles.	1,979
	Rear Axle Ratio - 4.11.	0
	Dual rear Bendix air disc brakes for dual rear axles to 46K capacity.	40
	Splined rotor for dual rear air disc brake for use with aluminum hubs.	-208
	Dual Rear Hubs: Aluminum hub pilot 46K 11-1/4 in. bolt circle.	0
	ConMet PreSet Plus Hub package; dual rear axle.	0
	Rear slack adjusters included w/ axle or air disc brakes.	0
	Spring brakes included w/ dual rear air disc brakes.	0
	Bendix 4S/4M anti-lock brake system w/ air traction control (ATC).	2
	Interaxle driveline 1 Dana SPL170XL	-4
	Wheel Differential Lock for Dana Spicer axles DSP40/DSP41(P)/DSH40(P)/DSH44(P)/D40-155 forward rear axle & rear rear. Under Speed Interlock is standard on T680.	37
	Rear suspension: Tandem Kenworth Airglide 400L 40K. 52 in. axle spacing. Air suspension w/ 8.5 in. ride height. Includes single leveling valve. Includes air suspension dump valve.	258
	LOW PROFILE SHOCK MOUNT ON AG460 F/BODY BUILDER INSTALL	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/27/2017 11:30:52 AM	***Complete***	Model Number:	T400 Series Conventional.
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q72765328
Prepared by:	ID: jervin		Version Number:	40.30

	Description	Weight
Tires & Wheels		
	Front tires: Bridgestone M860A 315/80R22.5 20PR. 42.8 in. diameter, all position. 19.9 in. SLR.	94
	Rear Tires: Bridgestone M710 Ecopia 295/75R22.5 14PR. 40.6 in. diameter, drive. 18.9 in. SLR. Smartway certified. Code is priced per pair of tires.	32
	Rear Tire Quantity: 8	0
	Front Wheel: Alcoa 89U63 22.5X9 AL Ultra ONE Wheel.	-39
	Rear Wheel: Alcoa 88367 22.5x8.25 aluminum with Level One [TM] finish, hub-pilot mount. 7400 lb. maximum rating. Air disc brake compatible. Code is priced per pair of wheels.	-176
	Single Front Axle: 2 Polished wheels. Polished outboard surface of aluminum wheels.	0
	Dual Rear Axle: 4 Polished wheels. Polished outboard surface of outer dual or single aluminum wheels.	0
	Rear Wheel/Rim Quantity: 8	0
Frame & Equipment		
	Frame Rails: 10-5/8 x 3-1/2 x 5/16 in. Steel to 337 in. to 416 in. Truck frame weight is 2.91 lb.-in. per pair of rails. Section modulus is 14.80, RBM is 1,776,000 in-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	367
	Full Steel Insert: for 10-5/8 in. or 10-3/4 in. Steel 337 in. to 416 in. or 2nd insert for 11-5/8 in. steel frame. Adds 1,149,000 in-lb to main rail RBM. Truck insert weight is 2.05 lb.-in. per pair of rails. Full frame insert length is equal to wheelbase plus rear frame cutoff plus dimension forward of front axle by model: T660, T680, T800, T880 = 21.26 in.; C500B = bumper setting minus 0.79 in.; W900B = 5.27 in., W900L = 1.50 in., W900S = 3.27 in.; T440/T470 50 in. bumper setting = 21.26 in., T470 73 in. bumper setting = 72.3 in.	748
	Bumper: Tapered chrome steel channel. Requires a bumper setting code.	5
	50 in. Bumper setting. Requires a bumper code.	0
	Front tow hook: Center mounted, cast. Requires iron front drive brackets.	28
	Front mudflaps.	0
	Custom Frame Layout: one chassis CFL F/T SAME AS 192858 CFL C/M SAME AS 192858 CFL A/D SAME AS 192858 CFL A/T SAME AS 192858 CFL BBX SAME AS 192858 CFL DEF SAME AS 192858	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/27/2017 11:30:52 AM	***Complete***	Model Number:	T400 Series Conventional.
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q72765328
Prepared by:	ID: jervin		Version Number:	40.30

	Description	Weight
	Steel cantilever battery box BOC w/ smooth aluminum cover. Vocational Style.	39
	Battery box location: LH Side.	0
	T470, C5, T6, T8 polished DPF/SCR or CNG cover with step. For use w/ 2010 or later exhaust systems. For T8, use extended length polished battery box on opposite rail to match the length of under cab components.	0
	First - LH outside rail only. Clear frame space area. Does not include fasteners or piping. Requires a supplemental length and location code. The actual chassis layout will be determined at time of engineering.	0
	Directly behind the under cab component. First clear frame space location.	0
	First - 12 in. clear frame space length. The impact to other frame-mounted components will be determined at time of engineering.	0
	Rear mudflap arms: Betts B-25 standard-duty, straight. Includes B1732 mounting brackets as standard.	0
	Rear mudflap shields: White plastic antisail w/ Kenworth logo.	0
	Square end-of-frame w/o crossmember; non-towing.	0
Fuel Tanks & Equip		
	Fuel Tank: 100 US gallon 24.5in. aluminum under replace. Class 8 fuel tanks w/ o locking caps include an anti-siphon device on the filler neck.	-23
	Small round DEF tank. 11 gallons of useable volume. The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	0
	6 in. wide lower fuel tank step, for one 22 in. or 24.5 in. tank LH.	2
	Polish only one aluminum tank.	0
	Polished cover for 1 DEF tank any size.	3
	Polished stainless steel tank straps for 1 tank.	0
	Standard DEF to fuel fill ratio: 2:1 or greater.	0
	Anti-siphon device swaged in place. For any number of fuel tanks.	1
	DEF tank location is on the RH.	0
	Location: 100 gal fuel tank LH under cab	0
Cab & Equipment		

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/27/2017 11:30:52 AM	***Complete***	Model Number:	T400 Series Conventional.
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q72765328
Prepared by:	ID: jervin		Version Number:	40.30

	Description	Weight
	Cab: Extended Day Cab w/ Curved Glass. Includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinge & pins. C500B: 129 in. BBC. 80 in. FA to BOC. T660B: 128 in. BBC. 80 in. FA to BOC. T800B: 127 in. BBC. 80 in. FA to BOC. W900B: 126 in. BBC. 96 in. FA to BOC. W900L: 136in. BBC. 106 in. FA to BOC.Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection, short and open check diagnostics, and programmable daytime running lights. Warning alarm will sound when lights are left on.	174
	Hood: Sloped Aerodynamic T440 Hood. Includes hood and mounted grille, split fenders w/ mudflaps, & separate bumper.	0
	Cab heater: W/integral defrosters & A/C 45,000 btu cab heater. No sleeper heater/AC. Includes 5 mode rotary control. T660 include filter media.	0
	Steering wheel: 18 in.4-spoke leather. Smartwheel multiplex steering wheel controls.	2
	Adjustable telescoping tilt steering column.	10
	PTO air control: On dash w/indicator light.	0
	Information for customer-installed PTO Chelsea 277. 10-bolt. Available only with Allison 3000/4000 series transmissions.	0
	Switch & Wiring for Customer-Installed PTO. Electric over hydraulic PTO. Includes switch guard. Wiring is routed to LH frame for connection to the customer installed PTO. No air controls are provided with this code.	0
	FLIP VLV/PPG: Bendix work brake f/frt &	0
	Five spare switches: Wired to power.	0
	Gauge: Air suspension pressure gauge.	0
	Gauge: Axle oil temperature, dual-drive axle. (2 gauges) w/integral warning light.	0
	Gauge: Oil Temperature Gauge Transmission. The NavPlus HD unit includes a virtual transmission oil temperature gauge.	0
	KW Driver Information Center: Includes fuel economy, RPM display, trip information, truck information, diagnostics, gear display, alarm clock.	0
	Instrument package: Includes speedometer, tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/27/2017 11:30:52 AM	***Complete***	Model Number:	T400 Series Conventional.
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q72765328
Prepared by:	ID: jervin		Version Number:	40.30

	Description	Weight
	Large flat panel on dash For customer-installed controls. Reduces gauge count by 6.	0
	Cab Interior: Summit. T440/T470 Only. Includes smooth upholstered side & back panels w/stitched accent lines, upholstered door pads, full vinyl headliner, black dash panels & black rubber floormats.	0
	Interior color: Jet Black w/Dark Slate Gray.	0
	Driver seat: Kenworth Air cushion Plus HB vinyl. Standard features includes 7 in. fore and aft slide adjustment w/isolator, 6-23 degree recline, air suspension with cover, dual armrests, and single chamber air lumbar support. Seat cushion is 20 inches wide w/ 2-position tilt and 2-position front cushion extension. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted and includes a map pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	0
	Rider seat: Kenworth Toolbox Plus HB vinyl. Standard features include fixed base and backrest, tool box seat base w/ door, and dual armrests. Seat cushion is 19.5 inches. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted with a map pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	0
	Seat color: All Jet Black.	0
	Kenworth Radio with AM/FM/WB/CD/USB and Bluetooth	4
	CB Radio: Cobra 29. Includes weatherband w/header mounted quick release. Includes transceiver & separate speaker remote-mounted in headliner & dual CB antennas. Includes sound tracker & illuminated panel.	11
	Speakers: Four 4 in. x 6 in. high performance. Adds 2 speakers to the Panasonic standard 2. Located in cab header & rear cab corners.	0
	Logbook holder under dash.	0
	Under dash center console: Includes one cupholder & two 12V outlets. For use w/Autoshift, Ultrashift, & Allison Gen IV only.	0
	Non-self cancelling turn signal: W/column-mounted headlight dimmer switch & intermittent wiper control.	0
	Electric LH & RH door locks.	0
	Remote Keyless Entry	0
	Stainless steel permit panels on cab.	13
	Cab access contoured grabhandles, LH/RH.	0
	Grabhandle: LH inside door frame above dash.	0
	Grabhandle: RH inside door frame above dash.	0
	Grabhandle: LH w/ short extension over door.	4
	Grabhandle: RH w/ short extension over door.	2
	Daylite Door: LH/RH includes RH peeper window	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/27/2017 11:30:52 AM	***Complete***	Model Number:	T400 Series Conventional.
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q72765328
Prepared by:	ID: jervin		Version Number:	40.30

	Description	Weight
	Dual rectangular air horn 23 in. LH & RH top of roof. Includes air horn covers.	4
	Look-Down, Pass. Door, Stainless 8.5x4.4	0
	Mirror: Dual Kenworth aerodynamic heated motorized 7 in. x 13 in. mirror w/ chrome shell. LH/RH convex mirrors 5 in. x 7 in. heated. Mirror brackets set for 8 1/2 ft load width. Switch located on door pad.	26
	Electric-powered LH & RH door window lifts. Switch located on door.	0
	Two corner & one rear cab stationary windows 17.5 in. x 16 in. (two) & 17 in. x 36 in. (one).	15
	One-piece windshield, w/ curved glass.	0
	Exterior stainless steel sunvisor.	11
	2 in. rubber wheelwell fender extension.	8
	Link Cabmate suspension.	22
Lights & Instruments		
	Headlamps: High Intensity Discharge (Xenon) Projector Module Low Beam, Halogen Complex Reflector High Beam.	0
	Marker Lights: Five, rectangular, LED	0
	Turn Signal Lights: Mounted on fender	0
	Halogen Spotlight: LH mounted.	4
	Combination Stop, Tail, Turn & Backup Lights RH & LH.	0
	Stainless Steel Brackets, Switch & Wiring: Customer-installed dual beacon lights mounted over door of cab with insulators.	4
	LH Courtesy Lamp: On upper skirt to light up step.	0
	Reflectors: Two Midframe	0
	Junction Box: Mounted Behind Cab or Sleeper Not Mounted at End of Frame.	1
	Circuit Brakers: Replacing fuses. Does not apply to any 5-amp fuse box position. Brakers include stop/brake/turn, tail lamp, high & low beams, marker/clearance lamps, horn, fuel heat, gauges, air dryer, HVAC controls, panel lamps. Some circuits will remain fuses.	0
Air Equipment		
	Air Dryer Bendix AD-IS heated Puraguard	0
	Moisture ejection valve w/ pull cable drain.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/27/2017 11:30:52 AM	***Complete***	Model Number:	T400 Series Conventional.
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q72765328
Prepared by:	ID: jervin		Version Number:	40.30

	Description	Weight
	Full truck kit: Gladhands mounted at end-of- frame.Seven-way female receptacle mounted at end-of-frame in taillamp bracket. Kit includes dash mounted trailer air supply valve, trailer hand control valve, and hoses/fittings for the valves. Dash mounted parking brake valve, tractor protection valve, and spring brake inversion/relay valves are standard.	15
	Nylon air tubing in frame & cab, excluding hoses subject to excessive heat or flexing.	0
	Locate air dryer inside RH rail BOC. This code requires the use of a custom frame layout code.	0
	Air tanks: clear of left side of transmission area. This code requires the use of a custom frame layout code.	0
	Trailer ABS electric supply through SAE J560 7-pin connector per TMC RP137).	0
Extended Warranty		
	Standard Warranty.	0
Miscellaneous		
	Local PDI then Ship to Specific Address. N94000 Local PDI N94010 Champion Carriers N94020 2991 KIRILA ROAD N94030 HERMITAGE , PA 16148 N94040 STEVE BURNS 724-981-3328	0
	GHG Secondary Manufacturer: Does Not Apply	0
	Warning triangle reflector kit: Shipped loose. Kit consists of 3 triangles in plastic carrying case. Not floor mounted.	4
	One 5 lb. dry chemical type fire extinguisher mounted outboard of driver seat. Class ABC.	11
Paint		
	Paint color number. N97020 A - L0006 WHITE N97200 FRAME N0001 BLACK	0
	Bumper Unpainted	0
	Day Cab Standard Paint	0
	1 - Color Paint - Day Cab Color will be White if no other color is specified.	0
	Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/27/2017 11:30:52 AM	***Complete***	Model Number:	T400 Series Conventional.
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q72765328
Prepared by:	ID: jervin		Version Number:	40.30

Total Weight	16080 lb

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	10/27/2017 11:30:52 AM	***Complete***	Model Number:	T400 Series Conventional.
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q72765328
Prepared by:	ID: jervin		Version Number:	40.30