

**Standard Options**

- Engine - HINO J08E-VB 6 cylinder, 260 HP Turbo Inter-Cooled.
- INSIGHT hardware. 1 year telematics. 5 years remote diagnostics.
- Engine block heater (1000W / 120ACV)
- Oil capacity - 16.15 quarts.
- Exhaust Brake - Driver controlled w/steering column Stalk Switch
- Fuel Filter - Davco 243 Diesel Pro Heated fuel/water separator. (Diesel Pro 243)
- Alternator – Delco 12 volt 130 amp Brush Type
- Battery - Two 12 volt parallel connection, 600 CCA x 2. GR31
- Starter – Denso 12 volt 4.8 kW / 6.4 HP rating
- Radio - AM/FM with single CD, bluetooth, two speakers.
- Air Conditioning - Denso Cab AC System designed specifically for Hino - Refriger
- Meter Cluster - Information display: Instant and trip fuel consumption, Diesel
- Gauges - Speedometer, odometer, tachometer. fuel, coolant, and air pressure guag
- Grille - Chrome plated
- Heater/Defroster - 18,357 BTU/h.
- Lighting - Marker lamps, stop/tail lights, back-up lights, side-flasher lights.
- Cab Features - Cruise control, power steering, tilt and telescopic steering whee
- Warning Indicators - Oil pressure, brake pressure, coolant level, battery charg
- Cooling Capacity - 7.075 gallon cooling system capacity
- Warranty - see details below
- Hino Watch Roadside Assistance - 3-year unlimited roadside assistance including
- Fuel Tank - Aluminum 50 gallon capacity. Clean CA position. (drivers side mounte
- GVWR - Gross Vehicle Weight Rating - 25,500 lbs.
- Air Tank - Two 34 liter tanks (68L total),(15cfm@1250rpm)
- Brakes - Full air dual circuit "S" cam type with automatic adj. and Antilock Bra
- Air Dryer - Bendix –AD-IS (Air Dryer Integrated Solution) heated air dryer.
- Frame: Straight C Channel, powder coated, 34" width, yield 80K PSI, RBM 1,031,90
- Bridgestone Tires, Front 245/70R19.5 Rib. Rear: 245/70R19.5 Lug
- Front Axle - Meritor MFS10, 10,000 lb. capacity, Reverse Elliot "I" beam oil lu
- Front spring: 8,000 lb. rating. Rear spring: 19,000 lb. rating.
- Rear Axle Ratio - Standard 4.11

212" WB / 144.6" CA  
Auto - Allison 2200RDS w/Syn Fluids (PTO). w/ FuelSense

**Optional Equipment**

- 260HP Engine
- PTO Setting @ 1200 RPM
- Fabric Seats with bench passenger.
- Power Windows & Power Door Locks.
- Side Mirrors - Power Heated Chrome Mirrors.
- Air horn.
- Air Susp. - Hendrickson.
- Alcoa polished alum wheels (rear inner steel).
- Bumper - Chrome. 1 tow hook
- Bumper Hook - 2 Hooks
- 5 year 300,000 engine and emissions warranty

**Warranty/Hino Watch**

Warranty:



**Hino Watch:**

-3-year unlimited roadside assistance including: (lockout, \*out of fuel/DEF, battery jumpstart, information, and 2 year warranty towing). \*Fluids are customer pay responsibility.

[lynchtruckcenter.com](http://lynchtruckcenter.com)





Model	2020 Hino 258ALP
Transmission	Auto - Allison 2200RDS w/Syn Fluids (PTO). w/ FuelSense
Wheelbase	212.0

Standard Options		
Qty	Order Code	Description
1	ENGINE	Engine - HINO J08E-VB Turbo charged and intercooled with glow plugs, 6 cylinder, In-line water-cooled; Max Output 260hp @2500rpm; Max Torque 660lb.ft. @ 1500rpm; 7.68L displacement, EPA10 Emissions Certified.
1	INSIGHTSTD	INSIGHT hardware. 1 year telematics. 5 years remote diagnostics.
1	BLHZASTD	Engine block heater (1000W / 120ACV)
1	OIL	Oil Capacity - 16.15 quarts
1	EXHBRAKE	Exhaust Brake - Driver controlled w/steering column Stalk Switch
1	FUELFILT	Fuel Filter - Davco 243 Diesel Pro Heated fuel/water separator. (Diesel Pro 243)
1	ALT	Alternator – Delco 12 volt 130 amp Brush Type
1	BATTERY	Battery - Two 12 volt parallel connection, 600 CCA x 2. GR31
1	STARTER	Starter – Denso 12 volt 4.8 kW / 6.4 HP rating
1	RADIO	Radio - AM/FM with single CD, bluetooth, two speakers.
1	AIRCOND	Air Conditioning - Denso Cab AC System designed specifically for Hino - Refrigerant 134A
1	DISPLAY	Meter Cluster - Information display: Instant and trip fuel consumption, Diesel Particulate Reduction System performance/status, maintenance intervals, engine and vehicle diagnostics.
1	GAUGES	Gauges - Speedometer mph (km/h), odometer, fuel/DEF gauges, coolant temp gauge, engine tachometer, air pressure gauge.
1	FTGRILL	Grille - Chrome plated
1	HEAT/DEF	Heater/Defroster - 18,357 BTU/h
1	LAMPS	Lighting - Marker lamps, stop/tail lights, back-up lights, side-flasher lights.
1	MISC	Cab Features - Standard: Cruise control, power steering with tilt and telescopic steering column, cup holders, cigarette lighter, coat hook, bag hook, two overhead compartments, two door pockets, sun visors, side mirrors (1 flat, 1 convex) each side.
1	INDICATORS	Warning Indicators - Oil pressure, brake pressure, coolant level, battery charge, high beam, turn signal, parking brake, engine control

Standard Options			
Qty	Order Code		Description
			system and ABS.
1	FREIGHT		Equalized Freight Charge
1	COOLSYS		Cooling Capacity - 7.075 gallon cooling system capacity
1	WARRANTY_05		Warranty - Basic Vehicle-24 months unlimited mileage; Engine-36 months unlimited mileage; Engine-60 month Extended Coverage, 250,000 miles (includes injectors, fuel supply pump and turbo); Emission-60 months 100,000 miles; Frame Rails & Cross Members-48 months unlimited mileage; Cab-48 months unlimited mileage; ABS-24-36 months 300,000 miles.
1	HWATCH_05		Hino Watch Roadside Assistance - 3-year unlimited roadside assistance including lockout, *out of fuel/DEF, battery jumpstart, information, and warranty towing (2 year coverage). *Fluids are customer pay responsibility. Tire Service - assist customer in arranging for roadside tire service if requested
1	FUELTKN		Fuel Tank - Aluminum 50 gallon capacity. Clean CA position. (drivers side mounted)
1	GVWR		GVWR - Gross Vehicle Weight Rating - 25,500 lbs.
1	AIRTANK		Air Tank - Two 34 liter tanks (68L total),(15cfm@1250rpm)
1	BRAKES		Brakes - Full air dual circuit "S" cam type, leading and trailing shoes with automatic adjustment and Antilock Brake System (ABS). Front Brakes: 15.0" diameter x 4.0" x 0.73" thickness: Rear Brakes: 16.5" x 7.0" x 0.85".
1	AIRDRYER		Air Dryer - Bendix –AD-IS (Air Dryer Integrated Solution) heated air dryer.
1	FRAME		Frame - Straight C Channel frame, ladder type, powder coated, 34" wide, yield strength 80,000 PSI, resistance bending moment (RBM) 1,031,900 in./lbs. (one side no reinforcement).
1	TIRES		Front tires - Bridgestone 245/70R19.5 R250F Rib pattern; Rear tires - Bridgestone 245/70R19.5 M729F Lug pattern.
1	AXLES		Front Axle - Meritor MFS10, 10,000 lb. capacity, Reverse Elliot "I" beam oil lubricated hubs. Rear Axle - Meritor MS19-14X, 19,000 lb. capacity, full-floating single reduction single speed hypoid gearing.
1	SPRINGS		Front Spring: Tapered leaf springs with shock absorbers, 8,000 lb. rating; Rear Spring: Semi-elliptical main, 17,500 lb. rating.
1	AXLESTD		Rear Axle Ratio - Standard 4.11

Premium/Upgrade Options			
Qty	Order Code		Description
1	258ALP-20N		212" WB / 144.6" CA
1	KBGRDS		Auto - Allison 2200RDS w/Syn Fluids (PTO). w/ FuelSense
1	260HP		260HP Engine
1	RPM1200		PTO Setting @ 1200 RPM
1	SEAT3F		Fabric, w/two man passenger bench seat.



Premium/Upgrade Options		
Qty	Order Code	Description
1	PWDL	Power Windows & Power Door Locks.
1	MRRCH	Side Mirrors - Power Heated Chrome Mirrors.
1	HORZA	Air horn.
1	D68AR	Air Suspension - Hendrickson
1	Z05XC	Alcoa polished aluminum wheels (4 wheels - inner rear steel).
1	BMPC	Bumper - Chrome. 1 tow hook
1	HOOK2	Bumper Hook - 2 Hooks
1	Extended Warranty	5 year 300,000 engine and emissions warranty

[lynchtruckcenter.com](http://lynchtruckcenter.com)